

# CARECLEAN QUICKSPLIT

**A solvent based quick separating oil and grease remover suitable for use in conjunction with oily water separators and where IMO rules are required.**

- \*Based on aliphatic hydrocarbon solvents, selected non-ionic and anionic surfactants which are biodegradable.
- \*Good cleaning properties and fresh odour.
- \*Its emulsion with water and oil breaks up within a very short period. Less than 15 ppm oil remains in the water and therefore the product meets the requirements of IMO.
- \*Suitable for the removal of most mineral oils, fats, greases and preserving agents.
- \*Safe to use on all common metals, painted surfaces, epoxy and zinc-sillicated coatings.
- \*Has the approval of major manufacturers for use in oil-water separators.
- \*It fulfils TS 6850-017, edition 4 of the German military force.
- \*High flashpoint.

## **Application:**

### **General maintenance**

Careclean Quicksplit is used to clean machinery, floor plates and bulkheads in engine rooms.

### **Tanks**

Careclean Quicksplit can be sprayed undiluted as a spotcleaner in tankcleaning (Marpol requirements).

## **Directions for use:**

### **General maintenance**

For cleaning in engine rooms etc., Careclean Quicksplit is used undiluted. Dampen the surface to be cleaned and let the product act for 5 - 60 minutes. Brush the surfaces occasionally and finally rinse them thoroughly with water at 50 - 60° C. For heavier contamination we recommend Careclean HD Split.

## **Tanks**

To be used as a spotcleaner to decrease the amount of slops. Spray the surfaces to be cleaned until they are thoroughly dampened with undiluted Careclean Quicksplit. Let the product act for 5-60 minutes, then rinse thoroughly with water at 50 - 60° C.

For detailed instructions on tank cleaning, refer to the Marine Care Tank Cleaning Manual. A range of support equipment is also available.

## **Immersion baths**

Careclean Quicksplit is applied undiluted at ambient temperature or up to a maximum of 55° C in a heated tank. Soak components for several hours, remove from the bath and rinse thoroughly with a waterjet.

## **Practical hint**

Where an oil-water separator is installed, collect the treated bilge water in the dirty water collecting tank. After a reasonable separating time suck the bilge water from the bottom of the tank and discharge overboard through the oil-water separator. This is the best way to keep within the IMO rule limits (max. 15 ppm oil in the discharge overboard).

**Note:** The use of emulsifying products (old style degreasers) will affect the separating properties of Careclean Quicksplit.

## **Properties**

Clear yellow brown colored liquid. Mixture of aliphatic hydrocarbons and biodegradable surface active agents. Non-emulsifiable in water.

The product is safe for use on all common metals.

Special gravity	: 0.792
Flash point PM CC	: above 61 °C
pH (1% solution)	: 7.0

*For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.*

The details of our products are given completely free of undertaking. Since their application lies outside our control we cannot accept any liability for the results.